



UV-1200 /UV-1200PC UV/VIS Spectrophotometer

Feature

- Single-chip microcomputer control, LCD Screen (128*64 Dots) can display multiple sets of data
- Large memory space can store multiple sets of data and curve
- Auto zero,100% adjustment function , auto wavelength adjustment
- Wrap lights, automatic filter change, large sample pool (5mm ~ 100mm)
- Standard samples having a maximum ten-point standard curve measurement functions built
- Direct input by K, B factor for quantitative measurement standard curve
- Can be directly input and the corresponding standard concentration values establish a standard curve for quantitative measurement
- Adjustable electric saving standard curve parameter measuring set, can save a plurality of standard curve
- Can be done any standard curve editor, convenient for use

Technical Specifications

Wavelength Range	200~1000nm	Wavelength Setting	Automatic
Band Width	2nm	Photometric Display Range	-0.3~3A
Wavelength Accuracy	±1.0nm	Display mode	LCD Screen (128*64 Dots)
Wavelength Repeatability	0.2nm	Detector	Import Silicon Photodiode
Photometric Accuracy	±0.3% τ	Light Source	Import Deuterium Lamp Import Halogen Lamp
Photometric Repeatability	0.15% τ	Power Requirement	AC 220V/50Hz,110V/60Hz
Stray Light	<0.05% τ (220nm NaI,340nm NaNO ₂)	Dimensions(L*W*H)	460×330×210mm
Stability	0.001A/h@500nm	Weight	11Kg
Photometric Mode	T,A,C,E		

Standard Configuration

- Spectrophotometer main unit 1 set
- 1cm quartz cuvette 2 pcs
- 1cm glass cuvette 4 pcs
- Dust cover 1 pcs
- Power line 1 pcs
- Instruction manual 1 pcs
- Software suite 1 set(UV-1200 optional,UV-1200PC standard)